










### Intended use

Thinner for the Mipa WBC mixing system to adjust the required spray viscosity.

Mixing ratio: Mipa WBC 2-Schicht-Basislack + 10-20% Mipa WBC-Verdünnung

Spreading rate: --

### Processing instructions

	<b>Colour</b> colourless						
	<b>Mixing ratio</b>	<b>Hardener</b>		<b>by weight (lacquer : hardener)</b>	<b>by volume (lacquer : hardener)</b>		
	--	--	--	--	--		
	<b>Hardener</b>	<b>for complete paintwork</b>		<b>for partial paintwork</b>			
	--	--	--	--	--		
	<b>Pot life</b>	--					
	<b>Thinner</b>	--					
	<b>Spray viscosity</b> gravity spray gun	<b>Airmix/Airless</b>					
	--	--					
	<b>Application mode</b>	<b>Application mode</b>	<b>Hardener</b>	<b>pressure (bar)</b>	<b>nozzle (mm)</b>	<b>spray passes</b>	<b>Thinner</b>
	--	--	--	--	--	--	--
	<b>Flash-off time</b>	--					
<b>Dry coat thickness</b>							
--							
	<b>Drying time</b>	<b>object temperature</b>	<b>dust dry</b>	<b>set to touch</b>	<b>ready for assembly</b>	<b>sandable</b>	<b>recoatable</b>
	--	--	--	--	--	--	--

---

### Note

---

<b>Storage:</b>	--
<b>VOC Regulation :</b>	--
<b>Processing conditions:</b>	from+ 10 °C and up to 80 % relative humidity. Ensure adequate air ventilation.
<b>Processing instructions:</b>	--