



Mipa Steinschlagschutz-Spray Auto-Spray

Product Information

D - 2/1113

Art.Nr.: 21386 + Colour Ref. Nr.

Mipa Steinschlagschutz-Spray is an overcoatable, durable elastic protection against stone-chips, corrosion, de-icing salt and mechanical wear. Also suitable as an anti-noise compound, sealing film and underbody protection. Reliable long-term protection for spoilers, skirting and doors.



Substrate:

Vehicle flooring, wheel arches, spoilers, sills etc.



Pretreatment / Cleansing:

Pre-cleansing with Mipa Silikonentferner

Characteristics:

Fast drying
Durable elasticity
No sagging, drips or runs
Once fully cured, re-coatable with all customary painting systems
Abrasion resistant
Excellent ant-noise properties
Resistance against ageing
Slight structure effect

**Colour /
Grade of Gloss:**

Light grey (0000) / black (0001)
Matt

Preparation:



Shake can vigorously until the mixing balls move freely!

Application:



Spray to test - Spraying distance approx. 25 - 30 cm
2 - 3 coats, dry film thickness 300 - 450 µm.

Flash-off:



After use:



Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Drying Times:



Drying:

Dust dry:

20 Min.

Re-coatable:

2 - 4 h

**Processing
Conditions:**

From +10°C and up to 80% relative air humidity.
Do not spray on the motor, gears, brakes etc.

Storage:

In tightly closed original containers at least 2 years shelf life

**VOC-
Regulation:**

EC limiting value for the product (cat. B/e): 840 g/l (2007)
This product contains a maximum of 510 g/l VOC [4.26 lbs/gal]

**Safety
Information:**

Read the corresponding Material Safety Data Sheet!

The data sheet is for information purpose only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.