



# Mipa Zink-Ausbesserungsspray

## Product Information

D - 1/0211

Art.Nr.: 682210000

Mipa Zinkausbesserungsspray is a special zinc-aluminium paint for the repair of minor faults on galvanised surfaces, for interior and exterior work. Excellent adhesion on iron and zinc, fast drying, weather and chalk resistant.



### Substrate:

Iron and galvanised surfaces



### Pretreatment / Cleansing:

Pre-cleansing with Mipa Silikonentferner

### Characteristics:

Excellent adhesion on iron and galvanised surfaces  
Fast drying  
Weather resistant  
Chalk resistant

**Colour /  
Grade of Gloss:**

Silver - RAL 9006

**Preparation:**



Shake can vigorously until the mixing balls move freely!

**Application:**



Spray to test - Spraying distance approx. 20 - 30 cm  
2 - 3 coats, dry film thickness 30 - 40 µm.

**Flash-off:**



2 - 3 min. between each coating

**After use:**



Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

**Drying Times:**



**Drying:**

**Dust dry:**

10 min.

**Set to touch:**

1 - 2 h.

**Full hardness:**

24 h.

**Processing  
Conditions:**

From +10°C and up to 80% relative air humidity

**Storage:**

In tightly closed original containers at least 2 years shelf life

**VOC-  
Regulation:**

EC limiting value for the product (cat. B/e): 840 g/l (2007)  
This product contains max. 690 g/l VOC [ 5.76 lbs/gal]

**Safety  
Information:**

Read the corresponding Material Safety Data Sheet!

The data sheet is for information purpose only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.